

POSH MAI 3,150 BHP / 49.4M / Utility Maintenance Vessel



Class Notation

ABS +A1, Offshore Support Vessel, (E), +AMS, UWILD, CRC, SPS, RW

Principal Particulars	
Flag	Singapore
Year Built	2016
Dlaca Duilt	D O F

Pax Ocean Engineering Pte Ltd, Zhuihai, China Place Built

Design Draft 2.90 m Max Summer Draft 3.50 m 1,285 T Gross Tonnage 385 T Net Tonnage

Deadweight (Max Draft) 710 T @ 3.5 m draft

Displacement 1,666 T 9812872 IMO No. PX1092 50 m Design TBA Call Sign

Dimensions

Length Overall 50 m Beam Overall 15 m Depth Moulded 5 m

Performance

Max Speed 11 - 12 kts* **Economical Speed** 8 - 10 kts*

* Subject to actual weather and operating conditions

Cargo Deck

Approx . 200m² Deck Cargo Area Deck Cargo Dimension About 11 m x 13 m

Deck Cargo Capacity 400T Deck Strength 3 T/m²

Reefer Points 4 (2 x 440v, 2 x 230v)

Capacities

Fuel Tank 240 m³ Fresh Water 140 m³

Discharging Rates

Fresh Water/Pump 90 m³/hr@20 m head Fuel/Pump 90 m³/hr@20 m head

Accommodation

1 man x 7 Berth Cabins 2 man x 11 Berth Cabins 22 3 man x 6 Berth Cabins 18 Total (POB) 47

Machinery & Equipment

Generators

Main Engines 2 x Caterpillar 3512C developing

970kW @ 1,200 rpm each (2 x 1,300bhp) 3 x Cummins KTA19-D(M1) 485kW each

Emergency Generator 1 x Cummins 6BT5.9-D(M) 91kW

Capstan 2 x 3T each

2 x Schottel SRP 1012FP Azimuth Propellers Propellers 2 x Kawasaki KT-32B3 Controllable Pitch 280kW each Bow Thruster

1 x Heela HMR240/30-2S SWL 20T @ 4m; Deck Crane

SWL 1.5T @ 30m

Oil Spill Equipment

Dispersant Capacity Foam Capacity

1 x 6-man SK45KFRPRescue Boat Rescue Boat

Life rafts 6 x 30-man

Life Buoys Life Jackets 56

POSH MAI

G-POSH Excellence Through Safety

3,150 BHP / 49.4M / Utility Maintenance Vessel

